

CORE™ and CORE+™ Panels

Our CORE™ and CORE+™ Panels offer a great performing, cost effective treatment solution when a white finish is required. CORE/CORE+ panels are covered on the face and on all sides with a classic white, textured finish that resembles painted drywall. The CORE+ panel offers an additional 1/8" high density fiberglass facing intended for rooms like gymnasiums where the panels might be exposed to impact.

Both the CORE and CORE+ panels have optional sheared edges for lay-in ceiling grid installations, as well as a foil backing option.

APPLICATIONS:

Restaurants, sales floors, houses of worship, multi-purpose rooms, and any other space that requires panels with a white finish.



SOUND ABSORPTION – DIRECT MOUNT:

Hz	125	250	500	1000	2000	4000	NRC
CORE 1"	.19	.44	.93	1.09	1.08	1.08	.85
CORE 2"	.37	.84	1.27	1.24	1.17	1.14	1.15
CORE+ 1"	.19	.44	.93	1.09	1.08	1.08	.90
CORE+ 2"	.64	.86	1.12	1.13	1.12	1.12	1.05

Note: Testing Data for CORE 1", CORE 2", CORE+ 1", CORE+ 2" Direct Mount



SPECIFICATIONS:

Core

6-7 pcf fiberglass

Thickness: 1" or 2"

CORE+: additional 1/8", high density fiberglass

Finishes

White Texture

Sizes

Custom sizes and shapes up to 4' x 8'

Mounting Options

Ceiling: Painted Pucks, Rotofast™ Snap-on Anchors, Z-clips, lay-in-grid

Wall: Rotofast™ Snap-on Anchors, Impaling Clips, Z-clips

Edges

Square, beveled

Hardened

Options

Sheared edges for lay-in grid, foil backing

Flammability

All components have a Class A rating per ASTM E84